

Armadillo Liners

PRODUCT DATA SHEET

Issue Date: 10/20/06

HPH-2BS Coating - High Pressure

Chemistry:

HPH-2BS is a MDI based polyurea hybrid two component 100% solids coating system.

Design:

HPH-2BS is a fast set, textured coating with excellent gloss retention and environmental resistance.

Equipment Requirement:

HPH-2BS requires 1:1 heated, high pressure, impingement spray application equipment capable of maintaining 1600psi. dynamic pressure and material temperature of 140°f.

Typical Areas of Application:

Truck Bed Liners
Recreational Vehicles and Trailers
Parking Garage Decks
Warehouse Floors
Walkways and Balconies
Manufacturing Facilities
Containment Basins
Flat Roofs

Handling and Storage

HPH-2BS should be stored inside at room temperature inside original sealed containers. Under these conditions, **HPH-2BS** will have a shelf life of 12 months in unopened, sealed container. Cured product may be disposed of without restriction, but local disposal ordinances must be followed. Product containers may be disposed of according to local, state or federal laws.

Precaution:

Read MSDS prior to using **HPH-2BS**. Basic safety precautions should be considered before installing this product such as the use of a fresh air supply system, appropriate gloves, clothing and protective eyewear. Keep out of reach of children.

Typical Properties:

Density	ISO = 9.7 lbs/gal POLY = 8.5 lbs/gal
Mixed Color	Black (Standard)
Solids	100%
Viscosity	ISO = 600-800 cps POLY = 600-800 cps
Shore Hardness	65
Tensile Strength	2800 psi
Elongation	50%
Tear Strength	300 pli
Tack Free	3-5 seconds
Full Cure	24 hours

The information contained in this data sheet has been determined through the application of accepted engineering practice and is believed to be reliable. Since conditions of application and use of our products are beyond our control, buyer shall determine the suitability of the product for buyer's intended use and assume all risk and liability arising out of such use. This information is furnished with the express condition that buyer will make its own tests to determine the suitability of the product for buyer's intended use. ARMADILLO LINERS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT THAT THE PRODUCT CONFORMS TO THE CHEMICAL DESCRIPTION ON THE LABEL. IN NO EVENT SHALL SELLER BE RESPONSIBLE IN ANY MANNER FOR PERSONAL INJURIES OR PROPERTY DAMAGE, OR ANY OTHER TYPE OR LOSS RESULTING FROM THE USE OF THIS PRODUCT. Nothing contained herein is to be considered to imply the non-existence of any relevant patents or to constitute permission, inducement, or a recommendation to practice any patented invention, covered by any patent, without permission or authority from the owner of the patent.

HPH-2BS

4650 FM 2920 Ste. C, Spring, TX 77388

Toll Free (866-339-6207) Fax (281)350-0588